

METHOD AND SYSTEM FOR ATM VIRTUAL CIRCUIT NUMBERING

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

[0001] The present invention relates generally to the field of optical networking.

DESCRIPTION OF THE RELATED ART

[0002] In order to serve the increasing bandwidth requirements demanded by modern communication applications, high-speed communications networks have been developed. The advent of certain technological advances, the movement from centralized systems to distributed computing, and worldwide standardization efforts, among other things, have led to the availability of high performance digital communications networks.

[0003] One such network is defined by a group of standards referred to as Asynchronous Transfer Mode (ATM). ATM technology and protocols allow for the integrated transmission of voice, data and video traffic simultaneously over high bandwidth circuits at speeds from T1 to OC-48 (2.5Gbps). Communication using ATM is accomplished through the switching and routing of packets of data referred to as cells, and a cell is a fixed-size packet of data. ATM networks are often used to provide high speed Internet access.

[0004] One particular type of ATM network makes use of optical waveguides in place of electrical conductors to carry the signals. Though most optical networks switch to electrical conductor transmission at the termination points, it would be beneficial from both a speed and a bandwidth perspective to provide entirely optical networks. While optical networks have become common in long-haul and metro area networking, they have not yet fully penetrated the local access portion of the network architecture. A particular example of a more local network is the PON (Passive Optical Networking) network. In this regard, the industry is working on the problems of providing so-called

fiber to the premises (FTTP) networks. FTTP networks, and in particular, point to multipoint FTTP networks are generally quite complex and the standards governing them require a number of addressing rules to be applied by service providers that install and maintain them. Thus, the inventors have determined that an automated system of handling numbering for ATM interfaces can find use in current and upcoming generations of optical networks.

SUMMARY

[0005] Embodiments may include a method that includes determining a communication port number corresponding to a particular communication port, determining a communication type corresponding to the communication port and selecting an identifying number that corresponds to the port and type. The identifying number includes particular bits that correspond to the port and other bits that correspond to the type.

[0006] Additional embodiments adhere to numbering rules set forth in standards governing ATM networks. Further additional embodiments make use of a system in which a group of low bits correspond to the port and a group of high bits correspond to the type.

[0007] Embodiments may also include a system that includes an communication network having a plurality of communication ports and allowing for a plurality of communication types, a network controller, functionally associated with the network, that makes use of identifying numbers associated with the plurality of communication ports and the plurality of communication types, and a processor, configured and arranged to select an identifying number for at least one of the plurality of communication ports or at least one of the plurality of communication types.

[0008] Furthermore, embodiments may include a machine readable medium encoded with machine executable instructions for performing a method including determining a communication port number corresponding to a particular communication

port, determining a communication type corresponding to the communication port and selecting an identifying number that corresponds to the port and type.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The invention claimed and/or described herein is further described in terms of exemplary embodiments. These exemplary embodiments are described in detail with reference to the drawings. These embodiments are non-limiting exemplary embodiments, in which like reference numerals represent similar structures throughout the several views of the drawings, and wherein:

[00010] FIGURE 1 is a block diagram of an example of a generalized PON network;

[00011] FIGURE 2 shows a table summarizing an example of a numbering scheme;

[00012] FIGURE 3 shows a table illustrating an example of another numbering scheme; and

[00013] FIGURE 4 shows a table illustrating an example of a further numbering scheme.

DETAILED DESCRIPTION

[00014] An embodiment of the present invention includes a system and method for providing network addressing using predetermined rule sets for use with a communications service. It may find particular application in optical networks, and in particular, point to multipoint networks including PONs, broadband PONs (BPONs) and gigabit PONs (GPONs).

[00015] In at least one embodiment, one such communications service may be an ATM based network that provides data services such as Internet Access to multiple subscribers.

[00016] Service providers may provide differentiated communications services to their users by providing ATM services in accordance with a particular ATM service category for different applications. For example, high speed Internet access may be

provided in accordance with the Unspecified Bit Rate (“UBR”) ATM service category. The UBR service category is intended for non-real-time applications (i.e., applications that can tolerate relatively high variations in cell transfer delay) and does not guarantee any particular CLR or CTD for the ATM service. Other types of service include continuous bit rate (CBR) service, non-real time variable bit rate (nrt-VBR) and real time variable bit rate (rt-VBR) service. The various service categories discussed herein may also be referred to as service types and other service types are contemplated as being within the scope of the invention.

[00017] FIGURE 1 shows a block diagram of an example of a PON network. A network interface separates the BPON network from a portion of a higher level network 102. The network interface may include, for example, an optical line termination (OLT) 104. The OLT may include, for example, hardware and/or software for providing virtual path, virtual circuit and cross connect functions. The OLT is further in communication with one or more optical network terminations (ONT) 106 or optical network units (ONU). As may be understood, the generic term “network termination” can be used in place of ONT, and the present invention is not restricted to use within an optical network, but may find an application in other types of network. The ONTs and/or ONUs each may include hardware and/or software for providing virtual circuit termination and virtual path cross connect functions, and may further include adaptation functions for interfacing with various other types of network interfaces such as Ethernet, for example. The network space between the OLT and ONTs can be referred to as the BPON network. Within the BPON network a system for numbering the virtual connections and virtual paths is used, thus the BPON numbering domain essentially includes that network space between the OLT and ONTs (or ONUs).

[00018] In at least one embodiment, the network is configured to provide communications in accordance with cell-switched communication standards and protocols such as, for example, ATM standards and protocols. In an embodiment, the network may provide Internet Protocol (IP)-based communications to support applications such as, but not limited to, Internet access. In particular, the network may be

configured to provide IP over ATM using ATM Switched Virtual Connection (SVC) in accordance with Internet Engineering Task Force (IETF) Request for Comment (RFC) 1577, for example.

[00019] Embodiments of the present invention generally find an application within the BPON numbering domain. In order to automate the process of assigning identifying numbers to either or both of virtual circuits and virtual paths within the BPON network, embodiments of the present invention provide a method of selecting numbers from a preset group.

[00020] Within the preset group, each number can be said to correspond to both a particular type of communication and a particular port. In the context of virtual path identifying numbers, each identifying number includes a portion that corresponds to a particular port identification and another portion that corresponds to a particular type of service.

[00021] For example, in the context of VPIs, each port identification may correspond to a particular ONT within the network. In general, a single OLT may serve several ONTs, for example, up to 64 ONTs may be served by one OLT. In this case, six bits would be required to specify uniquely the port identification.

[00022] Each type of service identification may correspond to a particular type of service. For example, four possible types of service are UBR, CBR, nrt-VBR and rt-VBR. If only four types of service are required, then two further bits can define the type of service. However, it may be useful to employ three or more bits to define the type of service in order to allow for future developments and other services. The ATM standard allows for up to 12 bits total for defining VPIs and up to 16 bits for VCIs. As a result, in the above-described system for defining VPIs, there are at least three bits left unused. These extra bits could be used to provide additional information, or may be reserved for use with various future developments. The table shown in FIGURE 2 summarizes an example of a numbering scheme in accordance with the above discussion.

[00023] As is clear from FIGURE 2, up to 64 ONTs may be individually identified using the low six bits of the identification number. Further, three higher bits are used to define the category, or type, of communication. Type 0 corresponds to UBR, type 1 to CBR, type 2 to nrt-VBR and type 3 to rt-VBR.

[00024] The top three bits remain unused. If, for example, a single OLT were to communicate with more than 64 ONTs, more bits could be used on the low end to identify the ONTs, making use of some of the reserved bits. Likewise, if the number of types of services were to increase beyond 8, some of the reserved bits could be used to define those services. Another possibility for future use of the unused bits is a broadcast VPI that communicates with each of the ONTs. In general, such a broadcast VPI should be a non-churned VP.

[00025] By way of example, ONT #3, carrying nrt-VBR communication would be assigned identifying number 131. That is, because the type is voice CBR, the seventh bit is 1, corresponding to 128. The low bits are 000011, corresponding to 3, the number of the ONT. Thus, the VPI number is 131, which is simply 128 plus 3. As will be evident from the table in FIGURE 2, for UBR type services the VPI number is always equal to the ONT number, as the high bits for UBR service are all zero.

[00026] Further examples are as follows: For ONT #15, UBR service, the VPI is 15; for ONT #10, CBR service: $VPI = 74$; For ONT #1, CBR: $VPI = 65$.

[00027] The table in FIGURE 3 illustrates an example of another numbering scheme to be used for assigning numbers to VCIs. According to this table, the low bits encode the port number while the high bits encode the port type.

[00028] In the case of an ATM network, the ATM standard excludes the use of port numbers 0-32 for defining a VCI. As a result, the application of the table in FIGURE 3 when applying that rule must make certain allowances and therefore results in some slightly different results than would the application of the table in FIGURE 2. One such scheme is detailed in the table shown in FIGURE 4.

[00029] Though the table of FIGURE 4 provides specific examples of the number of ports for each type, such examples are not meant to be limiting. As may be

seen, the table of FIGURE 4 describes a situation in which multiple VCCs are provided for the data ports, but certain other functions receive only a single VCC assignment. For example, even though in the table of FIGURE 4 particular channels are assigned fewer VCCs than others, they could instead be provided with the ability to make use of more, or indeed fewer VCCs. Additional types of circuits may be included, for example, specialized, proprietary data port types, video, additional types of voice circuits, diagnostic circuits, and the like.

[00030] As a further example, if data ports extended up to 32, rather than 24, as shown in the table of FIGURE 4, the table would change only slightly and would simply make use of the numbers between 223 and 255 by changing the formulae in the fourth column. Likewise, any of the available numbers could be split differently from those splits shown in the table of FIGURE 4. Furthermore, the unused bits allow for a far greater number of total VCIs and therefore ports than are shown in the table.

[00031] In order to further clarify the exemplary scheme illustrated in , some further examples are provided in which ordered pairs of the form {X,Y} are determined. Specifically, in each of the examples, X corresponds to a VPI number, while Y corresponds to a VCI number:

ONT #6, UBR service to Ethernet port, on 1 st VCC	{6, 37}
ONT #6, UBR service to Ethernet port, on 2 nd VCC	{6, 61}
• ONT #6, CBR service to Ethernet port, on 1 st VCC	{70, 37}
• ONT #6, Single voice Circuit	{70, 256}
ONT #2, OMCI CBR circuit	{66, 512}
• ONT #10, UBR circuit to 3 rd Ethernet port, on 1 st VCC	{10, 34}
• ONT #10, UBR circuit to 4 th Ethernet port, on 1 st VCC	{10, 35}
ONT #8, T1 port #2 over CBR	{72, 313}

[00032] While the invention has been described with reference to the certain illustrated embodiments, the words that have been used herein are words of description, rather than words of limitation. Changes may be made, within the purview of the associated claims, without departing from the scope and spirit of the invention in its aspects. Although the invention has been described herein with reference to particular structures, acts, and materials, the invention is not to be limited to the particulars disclosed, but rather can be embodied in a wide variety of forms, some of which may be quite different from those of the disclosed embodiments, and extends to all equivalent structures, acts, and, materials, such as are within the scope of the associated claims.

[00033] In particular, reference is made herein to ATM networks and to particular terms associated therewith. Nonetheless, the present invention may find use in other types of networks in which numbering schemes to identify particular paths or circuits may be employed.